EZ FABRIC CURVED COUNTER


PRODUCT CODE: EZ-CRVFABCTR



















PRODUCT DESCRIPTION

The EZ Fabric Counter display combines convenience and show. Push button snaps connect the lightweight aluminum frame. Place the frame into the fabric piece, cover and pull both zippers toward the back to enclose unit. Attach counter top. Graphics available on front, back, sides and top. See your printed graphic through the frosted acrylic counter top piece! This fully enclosed unit unzips to make for a convenient spot to hide stuff. Carry case included.

DISPLAY DIMENSION	46" W x 38" H x 18" L
GRAPHIC DIMENSIONS	82" W x 40" H

GRAPHIC MATERIAL

Stretch Fabric

GRAPHIC FINISHING

One piece. Inside hem. Two top zippers.

DISPLAY CONSTRUCTION

Aluminum Frame	Acrylic Counter Top

SHIPPING WEIGHTS & DIMENSIONS

	31 lbs (frame only) 33 lbs (with graphic)
Shipping Dimensions	49" H x 21" W x 7" D

LARGE QUANTITY FREIGHT

COANTITITICE		
Freight Shipping	20 boxes per 49" L x 40" W x 76" H skids	
Freight Weight	620 lbs (frame only)	

GRAPHIC TURN AROUND TIME

2 business days after proof approval

Curved Shelf	
AVAILABILITY	CA and PA
TOP WEIGHT CAPACITY	75 lbs
SHELF WEIGHT CAPACITY	7 lbs



Nylon Carry Bag



PARTS LIST




Qty 1 - Top Base (Pre-drilled for acrylic counter)



Qty 1 - Bottom Base



Qty 4 - 33" Vertical Support Bar



Qty 2 - 13.25" Horizontal Support Bar



Qty 1 - Acrylic Top Counter



Qty 2 - Large Head Bolt


REQUIRED TOOLS



Flathead Screwdriver*



Insert head bolt.



Then screw and tighten.

SET UP INSTRUCTIONS 1/2

Step 1

First, start by building both vertical sides of the EZ Fabric Counter.



Step 3

Set out your bottom base on a flat surface. Be sure not to confuse this base with the top, which has [2] pre-drilled holes for the acrylic counter top. Locate the push-out caps on the inside of the posts.



Step 5

The frame is now ready for the top base. Make sure it appears as shown above.



Step 7

Be sure that there is (1) pre-drilled hole on each side, facing up on the top base.



Step 2

Take (2) 33"support btars and (1) 13.25" support bar and connect them as shown above. Repeat the same process for another set.



Step 4

Push in and then hold the push-out cap on the bottom base so the support bar will slide on. Now slide each bar completely on to the bottom base. You will slide in one push-out cap at a time.



Step 6

Slide on the top base just as mentioned in step 4.



Step 8

The frame is now ready to be fitted with the graphic.



SET UP INSTRUCTIONS 2/2

Step 9

Starting from the bottom, slide the graphic on to the frame.



Step 11

Locate the pre-drilled hole on the top base. Make sure this hole aligns with the finished hole on the graphic.



Step 13

The install is now complete.



Step 10

Zip up the graphic around the frame.



Step 12

Align the acrylic counter top holes and insert the large head screws to secure the counter top to the frame.

